

HAND EXTRUDERS

HW-610 A | HW-610 B

HW 610 A

Hand Extruder



TECHNICAL PARAMETERS

Voltage	:	220V
Frequency	:	50/60Hz
Extruding Power	:	Drive Motor 1020W
Hot air drive power	:	1600W
Hot Air Temperature	:	20-600 degree C
Heating temperature while plastic extruding	:	200-300 degree C
Welding speed	:	2-3 kg/h
Diameter of Welding Rod	:	φ3.0mm-3.5mm
Weight	:	5.5kg

HW-610B

Hand Extruder



TECHNICAL PARAMETERS

Voltage	:	220V
Frequency	:	50/60Hz
Extruding Power	:	Drive Motor 1020W
Hot air drive power	:	3400W
Wind Temperature	:	20-600 degree C
Heating temperature while plastic extruding	:	200-300 degree C
Welding speed	:	2-3kg/h

UAE Distributor

Union Global Technical Equipment LLC

United Arab Emirates

Email : info@unionglobaltech.com

Phone:971-4-442-6684

HAND EXTRUDERS

HW-600A

HW-600B

Hiweld hand extruders are easy to use and extremely durable. There are four different models with various specifications satisfying every customer's unique requirements. They are extremely light and versatile and as such are useful in various types of fabrication including: containing tanks, fume treatment towers, scrubbers, chemical hoods, aspiration systems, manholes and for joining lining and geo textiles.

HW 600 A

Hand Extruder



TECHNICAL PARAMETERS

Voltage	:	220V
Frequency	:	50/60Hz
Extruding Power	:	Drive Motor 800W
Hot air drive power	:	1600W
Hot Air Temperature	:	20-600 degree C
Heating temperature while plastic extruding	:	200-300 degree C
Welding speed	:	2kg/h
Diameter of Welding Rod	:	φ3.0mm-3.5mm
Weight	:	5.5kg

HW 600 B

Hand Extruder



TECHNICAL PARAMETERS

Voltage	:	220V
Frequency	:	50/60Hz
Extruding Power	:	Drive Motor 800W
Hot air drive power	:	3400W
Hot Air Temperature	:	20-600 degree C
Heating temperature while plastic extruding	:	200-300 degree C
Welding speed	:	2kg/h
Diameter of Welding Rod	:	φ3.0mm-3.5mm
Weight	:	5.5kg

UAE Distributor

Union Global Technical Equipment LLC

United Arab Emirates

Email : info@unionglobaltech.com

Phone:971-4-442-6684