




**PE 100 SDR 11(PN16) & SDR 17(PN10)**  
Short Type Reducer (KIT Injection Welded)

Standard: TS EN 1555-3:2010 + A1 • TS EN 12201-3 + A1

Size (mm)	Pressure (Bar)	L (mm)	L1 (mm)	Z (mm)	Weight (kg)
d-d1					
710-400	PN 10	40	32	373	23,500
	PN 16	40	32	373	33,200
710-450	PN 10	40	30	318	21,950
	PN 16	40	30	318	30,910
710-500	PN 10	40	30	265	20,070
	PN 16	40	30	265	28,150
710-560	PN 10	40	100	200	16,070
	PN 16	40	100	200	22,210
710-630	PN 10	90	90	160	13,260
	PN 16	90	90	160	18,680




CONTINUE PAGE 2 AND PAGE 3



**PE 100 SDR 11(PN16) & SDR 17(PN10)**  
Short Type Reducer (KIT Injection Welded)

Standard: TS EN 1555-3:2010 + A1 • TS EN 12201-3 + A1

		L	L1	Z		
Size (mm)	Pressure (Bar)	(mm)	(mm)	(mm)	Weight (kg)	
d-d1						
800-400	PN 10	35	32	503	36,400	
	PN 16	35	32	503	55,100	
800-450	PN 10	35	30	448	34,850	
	PN 16	35	30	448	52,810	
800-500	PN 10	35	30	395	32,970	
	PN 16	35	30	395	50,050	
800-560	PN 10	35	100	330	28,970	
	PN 16	35	100	330	44,110	
800-630	PN 10	35	90	290	26,160	
	PN 16	35	90	290	40,580	
800-710	PN 10	35	70	150	12,900	
	PN 16	35	70	150	21,900	
900-400	PN 10	45	32	633	56,550	
	PN 16	45	32	633	83,590	
900-450	PN 10	45	30	578	55,000	
	PN 16	45	30	578	81,300	
900-500	PN 10	45	30	525	53,120	
	PN 16	45	30	525	78,540	
900-560	PN 10	45	100	460	49,120	
	PN 16	45	100	460	72,160	
900-630	PN 10	45	90	420	46,310	
	PN 16	45	90	420	69,070	
900-710	PN 10	45	70	280	33,050	
	PN 16	45	70	280	50,390	
900-800	PN 10	45	70	150	20,150	
	PN 16	45	70	150	28,490	





**PE 100 SDR 11(PN16) & SDR 17(PN10)**  
Short Type Reducer (KIT Injection Welded)

Standard: TS EN 1555-3:2010 + A1 • TS EN 12201-3 + A1

		L	L1	Z	
Size (mm)	Pressure (Bar)	(mm)	(mm)	(mm)	Weight (kg)
d-d1					
1000-400	PN 10	40	32	763	82,010
	PN 16	40	32	763	118,800
1000-450	PN 10	40	30	708	80,460
	PN 16	40	30	708	117,210
1000-500	PN 10	40	30	665	78,580
	PN 16	40	30	665	114,450
1000-560	PN 10	40	100	590	74,580
	PN 16	40	100	590	108,510
1000-630	PN 10	40	90	550	71,770
	PN 16	40	90	550	104,980
1000-710	PN 10	40	70	410	58,510
	PN 16	40	70	410	86,300
1000-800	PN 10	40	70	280	45,610
	PN 16	40	70	280	64,400

