




PE 100 SDR 11(PN16) & SDR 17(PN10)
Elbow 45° (Injection)

Standard: TS EN 1555-3:2010 + A1 • TS EN 12201-3 + A1



Size (mm)	Pressure (Bar)	L		Z		Weight (kg)
		(mm)	(mm)	(mm)	(mm)	
d						
20	PN 16	36	42			0,015
25	PN 16	40	50			0,025
32	PN 16	55	80			0,046
40	PN 16	55	85			0,080
50	PN 16	60	95			0,124
63	PN 16	65	90			0,210
75	PN 16	70	100			0,310
90	PN 16	80	120			0,540
110	PN 10	85	125			0,625
	PN 16	85	125			0,830
125	PN 16	90	135			1,205
140	PN 16	100	130			1,425
160	PN 10	100	160			1,600
	PN 16	100	160			2,185
180	PN 10	110	165			2,030
	PN 16	110	165			2,970
200	PN 10	115	180			2,915
	PN 16	115	180			3,840
225	PN 10	120	185			3,840
	PN 16	120	185			5,346
250	PN 10	130	210			5,193
	PN 16	130	210			7,120
280	PN 10	135	220			6,926
	PN 16	135	220			9,765
315	PN 10	145	240			9,895
	PN 16	145	240			12,585