



PE 100 SDR 11(PN16) & SDR 17(PN10)

EF Elbow 45°

Standard: TS EN 1555-3:2010 + A1 • TS EN 12201-3 + A1



Size(mm)	Pressure(Bar)	d1	L	L1	Z	Weight (kg)
		(mm)	(mm)	(mm)	(mm)	
d						
*32	PN 10-PN 16	44	119	32	87	0,154
40	PN 10-PN 16	54	52	42	10	0,105
50	PN 10-PN 16	67	58	45	13	0,170
63	PN 10-PN 16	81	67	49	18	0,245
75	PN 10-PN 16	94	83	62	21	0,433
90	PN 10-PN 16	114	90	64	26	0,655
110	PN 10-PN 16	138	108	78	30	1,155
125	PN 10-PN 16	153	109	77	32	1,255
*140	PN 10-PN 16	163	213	83	130	3,205
160	PN 10-PN 16	195	130	92	38	2,425
*180	PN 10-PN 16	222	152	105	47	4,160
*200	PN 10-PN 16	247	192	108	84	5,020
*225	PN 10-PN 16	273	160	120	40	6,750
*250	PN 10	302	332	122	210	13,993
	PN 16	302	332	122	210	15,920
*280	PN 10	350	345	125	220	19,826
	PN 16	350	345	125	220	22,665
*315	PN 10	380	373	133	240	25,895
	PN 16	380	373	133	240	28,585
*355	PN 10	410	360	129	231	26,780
	PN 16	425	360	129	231	36,046
*400	PN 10	460	384	131	253	35,210
	PN 16	490	384	131	253	49,060
*450	PN 10	510	471	162	309	55,060
	PN 16	555	471	162	309	78,882
*500	PN 10	570	509	175	334	73,080
	PN 16	615	509	175	334	102,516
*560	PN 10	640	441	175	266	80,940
	PN 16	685	441	175	266	121,760
*630	PN 10	720	460	180	280	101,240
	PN 16	780	460	180	280	168,700

*Products which marked are specially produced.